


Cast Y Strainer - Flanged

CY-E2

Schroeder Industries Class 150 ASME Flanged strainers are available in Carbon Steel and Stainless Steel. A machined, tapered seat ensures a perfect fit for the removable, stainless steel screen. Size 2" and larger come complete with flanged blow-off cover, gasket, and plug. 1-1/2" and smaller come complete with solid threaded cover and gasket. May be installed in vertical or horizontal pipelines with blow-off connection at the lower end of the screen.



Operating Pressures and Temperatures

Type	Size	psi @ Temp WOG
E2 150	1/2"-24"	285 @ 100°F

Standard Screens

Size	Standard	Opening
1/2"-1 1/2"	1/32" perf	0.032"
2"-3"	3/64" perf	0.045"
4"-24"	1/8" perf	0.125"

DIMENSIONS (Inches)

Size (in)	A	B	Blow-Off NPT	Shipping Weight (lbs)
1/2	6	2-9/16	1/4	9
3/4	7-1/2	3	1/4	11
1	7-3/8	3-3/8	1/4	15
1-1/2	7-1/4	4-3/4	1/2	18
2	8-5/8	4-7/8	1/2	30
2-1/2	10-1/4	7-1/2	3/4	44
3	11-5/8	7-3/4	1	60
4	14-1/4	9-1/8	1-1/2	96
5	17-5/8	11	2	150
6	18-5/8	13-3/8	2	174
8	24-3/8	14-5/8	2	264
10	26	17-1/4	2	414
12	30-3/8	21	2	615
14	36	27-3/16	2	720
16	46-9/16	30-1/4	2	956
18	46	35-11/16	2	1130
20	49-1/2	40	2	1500
24	58-3/8	44-1/2	2	1990

*Dimensions and Weights are for reference only. Please contact Schroeder Industries for certified drawings.

v.052925

How to Build a Valid Model Number for a Schroeder Y Strainer:

****Starting from the left to the right you will choose your Style and work your way through each category as illustrated above.**

120 SCHROEDER INDUSTRIES | PROCESS