



## Filter Model Number Selection



### How to Build a Valid Model Number for a Schroeder WQLF15:



**Example:** NOTE: One option per box



BOX 1	BOX 2	BOX 3	BOX 4
<b>Filter Series</b>	<b>Element Length (in)</b>	<b>Element Size and Media</b>	<b>Housing Seal Material</b>
WQLF15	39	QM60 = Q size 60 μ M media (reusable metal) QM150 = Q size 150 μ M media (reusable metal)	Omit = Buna N H = EPR V = Viton®

BOX 5	BOX 6
<b>Porting Options</b>	<b>Seal Material</b>
P48 = 3" NPTF	Omit = 30 psi cracking 50 = 50 psi cracking

BOX 7	
Dirt Alarm® Options	
	Omit = None
Visual	D5 = Visual pop-up D5C = D5 in cap <b>D9 = All stainless D5 (Recommended)</b> <b>D9C = D9 in cap (Recommended)</b> DPG = Differential pressure gauge
Visual with Thermal Lockout	D8 = Visual w/ thermal lockout D8C = D8 in cap
Electrical	MS5 = Electrical w/ 12 in. 18 gauge 4-conductor cable MS5LC = Low current MS5 MS10 = Electrical w/ DIN connector (male end only) MS10LC = Low current MS10 MS11 = Electrical w/ 12 ft. 4-conductor wire MS12 = Electrical w/ 5 pin Brad Harrison connector (male end only) MS12LC = Low current MS12 MS16 = Electrical w/ weather-packed sealed connector MS16LC = Low current MS16 MS17LC = Electrical w/ 4 pin Brad Harrison male connector
Electrical with Thermal Lockout	MS5T = MS5 (see above) w/ thermal lockout MS5LCT = Low current MS5T MS10T = MS10 (see above) w/ thermal lockout MS10LCT = Low current MS10T MS12T = MS12 (see above) w/ thermal lockout MS12LCT = Low current MS12T MS16T = MS16 (see above) w/ thermal lockout MS16LCT = Low current MS16T MS17LCT = Low current MS17T
Electrical Visual	MS13 = Supplied w/ threaded connector & light MS14 = Supplied w/ 5 pin Brad Harrison connector & light (male end)
Electrical Visual with Thermal Lockout	MS13DCT = MS13 (see above), direct current, w/ thermal lockout MS13DCLCT = Low current MS13DCT MS14DCT = MS14 (see above), direct current, w/ thermal lockout MS14DCLCT = Low current MS14DCT


**NOTES:**

Box 2. Replacement element part numbers are a combination of Boxes 2 and 3, and the letter V.  
Example: 39QM60V


Box 4. All elements for this filter are supplied with Viton® seals. Seal designation in Box 4 applies to housing only. Viton® is a registered trademark of DuPont Dow Elastomers.

Box 7. D9/D9C indicator is the recommended option.

## How to Build a Valid Model Number for a Schroeder WKF3



**Example:** NOTE: One option per box



BOX 1	BOX 2	BOX 3	BOX 4
<b>Filter Series</b>	<b>Number of Elements</b>	<b>Element Size and Media</b>	<b>Housing Seal Material</b>
WKF3	1 2 3	KM10 = K size 10 µ M media (reusable metal) KM25 = K size 25 µ M media (reusable metal) KM60 = K size 60 µ M media (reusable metal) KM150 = K size 150 µ M media (reusable metal) KM260 = K size 260 µ M media (reusable metal)	Omit = Buna N H = EPR V = Viton®

BOX 5	BOX 6
<b>Porting Options</b>	<b>Dirt Alarm® Options</b>
P = 1½" NPTF	Omit = None D = Pointer D5 = Visual pop-up <b>D9 = All stainless D5 (Recommended)</b>
	Visual D8 = Visual w/ thermal lockout
	Visual with Thermal Lockout D8 = Visual w/ thermal lockout
	Electrical MS5 = Electrical w/ 12 in. 18 gauge 4-conductor cable MS5LC = Low current MS5 MS10 = Electrical w/ DIN connector (male end only) MS10LC = Low current MS10 MS11 = Electrical w/ 12 ft. 4-conductor wire MS12 = Electrical w/ 5 pin Brad Harrison connector (male end only) MS12LC = Low current MS12 MS16 = Electrical w/ weather-packed sealed connector MS16LC = Low current MS16 MS17LC = Electrical w/ 4 pin Brad Harrison male connector
	Electrical with Thermal Lockout MS5T = MS5 (see above) w/ thermal lockout MS5LCT = Low current MS5T MS10T = MS10 (see above) w/ thermal lockout MS10LCT = Low current MS10T MS12T = MS12 (see above) w/ thermal lockout MS12LCT = Low current MS12T MS16T = MS16 (see above) w/ thermal lockout MS16LCT = Low current MS16T MS17LCT = Low current MS17T
	Electrical Visual MS = Cam operated switch w/ ½" conduit female connection MS13 = Supplied w/ threaded connector & light MS14 = Supplied w/ 5 pin Brad Harrison connector & light (male end)
	Electrical Visual with Thermal Lockout MS13DCT = MS13 (see above), direct current, w/ thermal lockout MS13DCLCT = Low current MS13DCT MS14DCT = MS14 (see above), direct current, w/ thermal lockout MS14DCLCT = Low current MS14DCT

## Filter Model Number Selection



WKC50

WLF1

WKF5

WKFN5

WRLT

WQF5

WQF15

WQLF15

WKF3

WKL3

### NOTES:

Box 3. Replacement element part numbers are identical to contents of Boxes 3 and 4.


Box 4. For options H and V, all aluminum parts are anodized. Viton® is a registered trademark of DuPont Dow Elastomers.

Box 6. D9 indicator is the recommended option.


## Filter Model Number Selection



### How to Build a Valid Model Number for a Schroeder WQLF15:



**Example:** NOTE: One option per box



BOX 1	BOX 2	BOX 3	BOX 4
<b>Filter Series</b>	<b>Number of Elements</b>	<b>Element Size and Media</b>	<b>Housing Seal Material</b>
WKL3	1 2 3	KM10 = 10 μ M media (reusable metal) KM25 = 25 μ M media (reusable metal) KM60 = 60 μ M media (reusable metal) KM150 = 150 μ M media (reusable metal) KM260 = 260 μ M media (reusable metal)	Omit = Buna N H = EPR V = Viton®

BOX 5	BOX 6
<b>Porting</b>	<b>Dirt Alarm® Options</b>
P24 = 1½" NPTF S24 = SAE-24 F24 = 1½" SAE 4-bolt flange Code 61 B24 = ISO 228 G-1½" P32 = 2" NPTF S32 = SAE-32 B32 = ISO 228 G-2"	Omit = None D5 = Visual pop-up <b>D9 = All stainless D5 (Recommended)</b> <b>D9C = D9 in cap (Recommended)</b> MS5SS = All stainless MS5 Electrical w/ 12 in. 18 gauge 4-conductor cable MS10SS = All stainless MS10 Electrical w/ DIN connector (male end only) MS13SS = All stainless MS13 Supplied w/ threaded connector & light

BOX 7	BOX 8
<b>Test Port Options</b>	<b>Bowl Drain Options</b>
Omit = None L = Two ¼" NPTF inlet and outlet female test ports	Omit = None DR = 7/16" -20 drain on bottom of housing

**NOTES:**

Box 4. Replacement element part numbers are a combination of Boxes 2 and 3, and the letter V.  
Example: KM10V

Box 5. All elements for this filter are supplied with Viton® seals. Seal designation in Box 4 applies to housing only. Viton® is a registered trademark of DuPont Dow Elastomers.

Box 6. D9/D9C indicator is the recommended option.

Contact factory for more Dirt Alarm® options